



### Accessible Large-Format FDM Printing

Industrial scale printing. Simplified.

Print big without the high capital investment of exclusive, large-format printers. The Stratasys F770<sup>™</sup> 3D printer makes printing large, complex parts affordable, reliable and easy.





REPRESENTED BY: Allegheny Educational Systems, Inc. 320 East 3rd Avenue Tarentum, PA 15084 Phone: 800-232-7600 www.alleghenyedusys.com



### Print large or print many.

The F770 is designed with size in mind. Print one or several large parts or take advantage of the printer's generous capacity to make multiple parts for maximum productivity.

With the longest fully heated build chamber on the market, you can print a part that is 46 inches long on the diagonal. The spacious 13 cubic-foot build envelope opens up new opportunities for manufacturing, prototyping and production-part part applications that aren't available with smaller printers.

There's no need to sacrifice on part complexity either. The F770 uses soluble support material, which lets you design and print your parts free from design-for-manufacturability constraints or the limitations of printers with inferior support capability. The hands-free support removal process also minimizes post-processing, increasing your productivity.





## Print-and-forget dependability.

Get accurate print results along with the repeatability and reliability that FDM Technology<sup>™</sup> is known for. Stratasys FDM build chamber design is time-tested, ensuring precise thermal management across the build platen. This gives you consistent, successful print results, whether parts are big or small.

You can easily control the material density options. Print with full density when you need the strength or use a sparser fill to save material and print time, a valuable option for very large parts. Variable slice height capability also lets you optimize your part's appearance while minimizing print time.

The F770 embodies the same industrial-grade components and design philosophy that make FDM Technology a class leader for reliability and consistent performance. It is proven technology that simply works.



# A printer anyone can operate.

3D printing with the F770 is straightforward and requires no specialized training. It's designed with plug-and-print simplicity so virtually anyone can print large, complex parts quickly and easily.

The user-friendly GrabCAD Print<sup>™</sup> software makes the CAD-to-print workflow simple, so all you have to do is import your CAD model and press the print button. It also features advanced capabilities and build options that help ensure successful results when printing large parts and tools. For those who want more in-depth print adjustment capability, Insight<sup>™</sup> software is also included, to provide the greatest control over print results.

3D printing with the F770 is also a lights-out, 24/7 operation. There's no need to constantly monitor the printer while it's operating. Quick-change material canisters are equipped with 200 cubic inches of filament, enabling up to 140 hours of unattended printing. When you do want to check progress, the F770's built-in camera provides continually updated static images of print status, and GrabCAD Print's monitoring feature lets you check this remotely from your mobile device.

# Print big for a not-so-big price.

Large-format printing doesn't have to break your budget. The F770 is designed to make reliable, largescale printing more accessible, with an affordable price. That's possible because not all 3D printing applications require highperformance materials or all the capabilities engineered into large, more expensive printers.

Instead, the F770 gives you access to widely used engineering-grade thermoplastic materials and Stratasys FDM reliability. It comes equipped with MTConnect, ready to plug into your smart factory floor. And it does all this in a large-format, easy-to-use platform, for the highest value available for 3D printing large, complex parts.



# Unmatched support, when you need it.

Stratasys invented FDM Technology and we've been perfecting it for over 30 years. Our technicians and application engineers have the knowledge to make the most of your printer investment and address problems when they occur.

When you need help, our global support staff is here to assist, from professional installations to application guidance to on-site troubleshooting. Whether it's optimizing your print results, solving a problem or providing training, Stratasys service and support has the experience and reach to keep you operational.

To learn more about the Stratasys F770, see the specifications below. Or contact a Stratasys representative by visiting <u>Stratasys.com/contact-us</u>.



### See the specs.

| F770 Printer and Material Specifications |   |
|--|---|
| System Size and Weight                   | 175 x 124 x 196 cm (69 x 49 x 77 in.)<br>658 kg (1450 lbs.)   |
| Build Envelope                           | 1000 x 610 x 610 mm / 372,000 cm³ (39.4 x 24 x 24 in. / 22,677 in³)   |
|  | Maximum length on the diagonal – 1,171 cm (46.1 in.)  |
| Materials                                | ASA – Ivory   |
|  | ABS-M30™ – Black  |
|  | SR-30™ soluble support material   |
| Material Delivery                        | 200 in <sup>3</sup> coil box (3277 cm <sup>3</sup> )  |
| Achievable Accuracy                      | XY part accuracy = +/- 0.254 mm (+/- 0.010 in.) or +/- 0.002 mm/mm (+/- 0.002 in./in.), whichever is greater                  |
|  | Z part accuracy = +/- 0.200 mm (+/- 0.008 in.) or +/- 0.002 mm/mm (+/- 0.002 in./in.), plus 1 layer height                    |
| Software                                 | GrabCAD Print, Insight, Control Center™, MTConnect enabled  |
| Workstation Compatibility                | Wired and wireless (with USB dongle) network interfaces using standard TCP/IP protocols at 100 MBPS minimum                   |
| Wireless Network Connectivity            | IEEE 802.11n-2009<br>IEEE 802.11g-2003<br>IEEE 802.11b-1999   |
| Operating Conditions                     | Operating temperature 15 °C to 30 °C (59 °F to 86 °F)<br>Operating Humidity 30-70% - 39 in. clearance on each side of printer |
| Audible Noise/Acoustics                  | 54 dBA  |
| Power Requirements                       | 3 phase, 208V, 30A, 5 wire, 47-63 Hz frequency  |
| Regulatory Compliance                    | CE, cTUVus, RCM, EAC, FCC Part B  |
| Facility Requirements                    | Double-door width for installation, vacuum pump within system – no shop air required, forklift uncrating and installation     |
| Installation Requirements                | Crate = 186.7 cm W x 146 cm D x 225.4 cm H (73.5 in. W x 57.5 in. D x 88.75 in. H)<br>Crated weight = 907 kg (2000 lbs)       |



#### **Stratasys Headquarters**

7665 Commerce Way, Eden Prairie, MN 55344 +1 800 801 6491 (US Toll Free) +1 952 937-3000 (Intl) +1 952 937-0070 (Fax)

stratasys.com ISO 9001:2015 Certified 1 Holtzman St., Science Park, PO Box 2496 Rehovot 76124, Israel +972 74 745 4000 +972 74 745 5000 (Fax)

© 2021 Stratasys. All rights reserved. Stratasys, the Stratasys Signet logo and FDM are registered trademarks of Stratasys Inc. F770, ABS-M30, SR-30, GrabCAD Print, Insight and Control Center are trademarks of Stratasys, Inc. All other trademarks are the property of their respective owners, and Stratasys assumes no responsibility with regard to the selection, performance, or use of these non-Stratasys products. Product specifications subject to change without notice. BR\_FDM\_F770\_0321a

